

Legend™ 412Z



Legend™ 412Z is a powerful and versatile LED wash fixture with an outstanding zoom range of 11° to 53°, making it perfect for the gamut of applications across the entertainment industry from touring to broadcast. The Legend™ 412Z features twelve 10-watt quad-color RGBW emitters with four zones of independent pixel mapping control, providing ultimate versatility in programming and use. Legend™ 412Z's light weight and road-worthy construction make it an excellent choice for rigs of any size and scope.

FEATURES

- 15, 27, 31 or 34 DMX channel fixture profiles
- 4 zones of LED control
- Fast and precise pan/tilt movement
- Versatile 11° to 53° zoom range
- 12 powerful 10 W long-life quad-color RGBW LEDs
- Strobe macros with quadrant control
- Neutrik® powerCON® power input/output connections
- 3- and 5-pin DMX input/output connections
- Flicker-free operation for wide market application including broadcast and film

SPECIFICATIONS

- DMX Channels: 15, 27, 31 or 34
- Data Connectors: 3- and 5-pin XLR
- Light Source: 12 LEDs (quad-color RGBW)
10 W, (2.9 A), 50,000 hours life expectancy
- Pan and Tilt: 540°/270°
- Automatic Pan/
Tilt Correction: Yes
- Built-in Automated Programs: Yes
- Customizable Programs: No
- Recall Custom Programs: No
- Shutter/Strobe: Electronic
- Strobe Rate: 0 to 20 Hz
- Standalone Color Mixing: Yes
- Color Temperature Presets: Yes
- Beam Angle: 8° to 33°
- Field Angle: 11° to 53°
- Zoom Angle: 11° to 53°
- Illuminance (11°): 3,880 lux @ 5 m
- Illuminance (53°): 330 lux @ 5 m
- Color Temperature (range): 2800 to 10000 K
- IP Rating: IP20, dry location
- Cable Length: 5 ft (1.5 m)
- Power Connection: Bare-wired to Neutrik® powerCON®
- Power Input: Neutrik® powerCON®
- Power Output: Neutrik® powerCON®
- Power Linking: 9 units @ 120 V; 15 units @ 208 V; 17 units @ 230 V
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 185 W, 1.5 A @ 120 V, 60 Hz
- Power and Current: 187 W, 0.9 A @ 208 V, 60 Hz
- Power and Current: 188 W, 0.8 A @ 230 V, 50 Hz
- Weight: 16.6 lb (7.5 kg)
- Dimensions: 7.21 x 10.67 x 13.98 in (183 x 271 x 355 mm)
- Approvals: CE, MET