

∞ Infinity MultiRay



KEY FEATURES

- Superior brightness
- MultiRay Beam effect
- 2000 W Fast Fit discharge lamp
- Electronically adjustable lamp power (800 W to 2000 W)
- Electronic strobe (ZAP Effect)
- Optical unit with extremely high luminous efficiency

SPECIFICATIONS

- MultiRay Beam effect
- Electronic strobe (zap effect), synchronized, random, pulse effect
- Pan 538°, Tilt 252°, 16 bit
- Mechanical black-out

PHYSICAL SIZE

- Length: 581 mm (22,9 in)
- Width: 510 mm (20.1 in)
- Height: 750 mm (30 in), head straight up
- Weight: 41 kg (90,4 lbs)

LAMP AND BALLAST

- Type: Philips MSR Gold™ 2000/2 FastFit 1CT
- Color temperature: 7500 Kelvin
- Color rendering index: 88 Ra8
- Average lamp life: 750 hours
- Socket: PGJX50
- Electronically adjustable lamp power (800 W to 2000 W)
- Electronic ballast with Power Factor Correction

CONTROL PROTOCOL AND PROGRAMMING

- USITT DMX512/1990
- Artnet
- DMX channels: 22
- Setting and addressing: LCD display or remotely RDM ready

ELECTRICAL SPECIFICATIONS/ CONNECTIONS

- AC power: 190-245 V, auto-sensing, 50/60 Hz, 2m (6.6 ft) integral cable without power plug
- Power consumption: 5.5-11.3 A at 240 V
- DMX data in/out: 3 pin and 5 pin locking XLR

10018F008