

# ∞ Infinity Profile XL



## KEY FEATURES

---

- 1500 W Fast Fit discharge lamp
- Framing system, adjustable over 180°
- Modular design for easy maintenance and servicing
- Optical unit with extremely high luminous efficiency

## SPECIFICATIONS

---

- CMY color mixing system
- 5 colors + open
- Proportional CTO
- Framing system, adjustable over 180°
- 1 aerial wheel, 6 rotating gobos + open
- 1 break-up wheel, 6 static gobos + open
- Focus
- Proportional zoom 8° - 35°
- Iris
- Dimmer (mechanical and digital)
- Mechanical strobe, electronic strobe (zap effect), synchronized, random, pulse effect
- Modular design for easy maintenance and servicing
- Pan 530°, Tilt 270°, 16 bit

## PHYSICAL SIZE

---

- Length: 450 mm (17.7 in)
- Width: 505 mm (19.9 in)
- Height: 880 mm (30.7 in), head straight up
- Weight: 51 kg (112.4 lbs)

## LAMP AND BALLAST

---

- Type: Philips MSR Gold 1500 Fast Fit
- Color temperature: 6000 Kelvin
- Color rendering index: 83
- Average lamp life: 750 hours
- Socket: PGJX50
- Electronic ballast with Power Factor Correction

## CONTROL PROTOCOL AND PROGRAMMING

---

- USITT DMX512/1990
- Artnet
- DMX channels: 32
- Setting and addressing: LCD display or remotely
- RDM ready

## ELECTRICAL SPECIFICATIONS/ CONNECTIONS

---

- AC power: 190 - 250 V, auto-sensing, 50/60 Hz, 2 m (6.6 ft) integral cable without power plug
- Power consumption: 8 A at 230 V
- DMX data in/out: 3 pin and 5 pin locking XLR

# 10014G006