

∞ Infinity Spot L



KEY FEATURES

- Compact and efficient solution with its 1000 W source
- HD quality projection, dimming & CMY
- New superfast zoom mode, from 30° to 6° in 1 s
- Fully equipped effects engine, including 2 rotating prisms
- Proportional frost
- Film frame effect

SPECIFICATIONS

- CMY color mixing
- 5 colors + open
- CTO filter
- 1 aerial wheel, 7 gobos + open
- 1 break-up wheel, 7 gobos + open
- 2 rotating prisms
- Focus
- Proportional zoom 6° - 30°
- Proportional frost
- Iris
- Dimmer
- Mechanical strobe, electronic strobe (zap effect), synchronized, random, pulse effect
- Modular design for easy maintenance and servicing
- Pan 540°, Tilt 284°, 16 bit

PHYSICAL SIZE

- Length: 466 mm (18.4 in)
- Width: 552 mm (21.7 in)
- Height: 756 mm (29.8 in)
- Weight: 35 kg (77.1 lbs)
- Un-compromised light weight despite unique and high resistant aluminium superior body ideal for rental use

LAMP AND BALLAST

- Osram HTI 1000/PS Lok-it (mounted)
- Color temperature: 5800 Kelvin
- Color rendering index: 85
- Average lamp life: 750 hours
- Socket: PGJ36
- Electronic ballast with Power Factor Correction

CONTROL PROTOCOL AND PROGRAMMING

- USITT DMX512A
- Artnet (optional)
- DMX channels: 23/24
- Setting and addressing: LCD display

ELECTRICAL SPECIFICATIONS/ CONNECTIONS

- AC power: 90 -250 V, auto sensing, 50/60 Hz, 2m (6.6 ft) PowerCon cable without power plug
- Power consumption 5.8 A at 230 V
- DMX data in/out: 3 pin and 5 pin locking XLR
- Ethernet RJ45 port

10022B010