

∞ Infinity Wash M



KEY FEATURES

- “MULTI-lamp” concept ready
- Bright as a 1200 W fixture, in a package 1/3 the size
- Zoom range from 42° down to 6°
- Moon flower aerial effect (Patent Pending)
- Space, weight, power saving
- Effect engine
- Artnet ready
- New digital ballast technology

SPECIFICATIONS

- CMY color mixing
- 5 colors + open
- CTO filter
- Beam shaper 360° (Patent Pending)
- 2 Prismatic effects: moon flower, beam’o (Patent Pending)
- Motorized optical effect zoom: 6° to 26°
- Motorized optical wide zoom: 8° to 42°
- Dimmer
- Mechanical and electronic strobe (zap effect), synchronized, random, pulse effect
- Modular design for easy maintenance and servicing
- Pan 540°, Tilt 284°, 16 bit

PHYSICAL SIZE

- Length: 459 mm (18.1 in)
- Width: 377 mm (14.8 in)
- Height: 602 mm (23.7 in), head straight up
- Weight: 25 kg (55 lbs)

LAMP AND BALLAST

- Type: GE 750W tungsten halogen lamp, Philips MSR Gold 575/2, Philips MSR Gold 700/2, GE CSR 700TAL Mini (mounted)
- Mini FastFit, MULTI-lamp ready
- Color temperature: 7400 Kelvin
- Color rendering index: 71
- Average lamp life: 750 hours
- Socket: PGJX28
- Digital electronic ballast with Power Factor Correction

CONTROL PROTOCOL AND PROGRAMMING

- USITT DMX512/1990
- Artnet, Artnet to DMX converter
- DMX channels: 18
- Setting and addressing: LCD display or remotely

ELECTRICAL SPECIFICATIONS/ CONNECTIONS

- AC power: 90 – 250 V, auto sensing, 50/60 Hz, 2 m (6.6 ft) integral cable without power plug
- Power consumption: 4.5 A at 230 V, 9.5 A at 115 V
- DMX data in/out: 3 pin and 5 pin locking XLR
- Ethernet RJ45 port