

∞ Infinity Wash S



KEY FEATURES

- Brighter than a 575 W fixture, in a package half the size
- Replace both 575 and 250 wash fixtures with one fully equipped moving light
- Space, weight, power saving
- Effect engine
- Amazing zoom range from 24° down to 4°
- Moon flower aerial effect (Patent Pending)
- Zoom tight as an ACL
- Silent operation for the quietest applications

SPECIFICATIONS

- CMY color mixing
- 5 colors + open
- CTO filter
- Beam shaper 360° (Patent Pending)
- 2 Prismatic effects: moon flower, beam'o (Patent Pending)
- Proportional zoom 4° - 24°
- Dimmer
- Mechanical and electronic strobe (zap effect), synchronized, random, pulse effect
- Modular design for easy maintenance and servicing
- Pan 540°, Tilt 284°, 16 bit

PHYSICAL SIZE

- Length: 459 mm (18.1 in)
- Width: 377 mm (14.8 in)
- Height: 602 mm (23.7 in), head straight up
- Weight: 23 kg (50.7 lbs)

LAMP AND BALLAST

- Type: GE Lighting CSR300/2/TAL
- Color temperature: 7700 Kelvin
- Color rendering index: 75
- Average lamp life: 750 hours
- Socket: PGJX28
- Electronic ballast with Power Factor Correction

CONTROL PROTOCOL AND PROGRAMMING

- USITT DMX512/1990
- Artnet, Artnet to DMX converter
- DMX channels: 18
- Setting and addressing: LCD display or remotely

ELECTRICAL SPECIFICATIONS/ CONNECTIONS

- AC power: 90 – 250 V, auto sensing, 50/60 Hz, 2 m (6.6 ft) integral cable without power plug
- Power consumption: 2 A at 230 V, 4.4 A at 115 V
- DMX data in/out: 3 pin and 5 pin locking XLR
- Ethernet RJ45 port