



The MAC Viper Performance is a full-feature framing fixture that delivers an output and performance never before seen in a fixture this size or one using so little power. Unlike other fixtures in this class, the MAC Viper Performance does not forgo an iris or animation wheel – they are both included along with a framing system and rotating gobos.

The framing system consists of four shutter blades that can all individually adjust +/- 30° while the entire system can rotate +/- 55°. The exacting system can repeat each cue with great precision. When fully focused, gobos can be nicely framed with a soft edge. The MAC Viper Performance has adopted the compact form, impressive speed, superior light quality and beautiful colors that the MAC Viper Profile is renowned for and uses the same 1000-watt lamp.

26000 Lumens – Excellent light quality with a very flat and uniform field and 6000K color temperature

1:5 zoom – Fast zoom with auto-linked focus

Four shutter blades individually adjust +/- 30° while the entire system rotates +/- 55°. Repeats cues with great precision

Large aperture front lens – The 140 mm front lens exceeds the size of any other fixture in this segment for just the right fat beam look

5 rotating gobos – All glass gobos with only a slight focal separation to the framing system

Animation wheel with continuous bi-directional rotation

CMY – Vibrant color mixing with a superior palette of colors including true reds, rich ambers, primary green and deep blues

7-slot color wheel – Static colors and correction filters for added color choice and bump effects

Linear CTO – Daylight to tungsten CCT control and expansion of the CMY palette

Dimmer and shutter - Combined dimmer/shutter system with intensity effects, instant blackout/open and smooth fades

Iris – Fast and tight iris with adjustable dynamic effects

Strobe – Diverse strobe effects using mechanical or electronic control or in combination

Soft frost – A light frost leaves gobo artwork visible with a beautiful soft edge. Includes a linear focus blurring option

4-facet prism – Real beam separation with rotation and index control for dynamic effects and accurate tiling

Physical Length (Head): 566 mm
Width: 472 mm
Width (Base): 335 mm
Height (head straight up): 731 mm
Height (maximum): 748 mm
Weight: 37.9 kg

Lamp Type: 1000 W short-arc discharge

Color temperature: 6000 K
CRI (Color rendering index): >85
Average lifetime: 750 hours
Socket: PGJX36
Ballast: Electronic
Approved lamps: Osram HTI 1000/PS Lok-it, Philips MSR Gold MiniFastFit 1000W

Dynamic Effects Color mixing: CMY, independently variable 0 - 100%
Color temperature control: CTO, variable 6000 - 3200 K
Color wheel: 7 interchangeable dichroic filters + open, indexing, continuous rotation, random color
Aerial wheel: 5 interchangeable texture/breakup gobos + open, indexing, continuous rotation and shake
Gobo animation: Interchangeable animation wheel, indexing, continuous rotation with variable speed and direction
Framing: Rotatable framing module, +/- 55°, with 4 individually controllable blades
Prism: Interchangeable 4-facet rotating prism
Iris: 0 - 100%
Frost: Variable
Mechanical dimmer/shutter: 0 - 100% continuous dimming, variable & random strobe & pulse effects, instant open & blackout
Dimming options: Choice of four dimming curves
Focus: Range varies with zoom angle, from 2 m / 6 m to infinity (approx.)
Zoom: 10° - 44°
Zoom-focus linking system: 3-zone
Pan: 540°
Tilt: 268°
Position correction system: Absolute position monitoring

Control and Programming DMX channels: 32/40
Setting and addressing: Control panel with backlit graphic display and jog wheel or via DMX
16-bit control: Dimming, rotating gobos, zoom, focus, pan and tilt
DMX compliance: USITT DMX512-A
RDM compliance: ANSI/ESTA E1.20
Receiver: Opto-isolated RS-485
Firmware update: USB memory device or USB/DMX hardware interface over DMX link

Service Utilities Fixture identification: User-settable fixture ID number

Construction Color(s): Black
Housing: UV-resistant fiber-reinforced composite
Reflector: Glass, cold light
Protection rating: IP20

Gobos Size: E27 (Size E, max. image diameter 27 mm)
Approved material: Borosilicate 3.3 or better with dichroic or heavy matted aluminum coating (metal gobos not approved)
Outside diameter: 37.5 mm +/- 0.2 mm
Maximum image diameter: 27 mm
Maximum thickness: 1.1 mm +/- 0.1 mm

Installation Mounting points: Eight quarter-turn locking points
Orientation: Any
Minimum distance to illuminated surfaces: 3.4 m
Minimum distance to combustible materials: 0.3 m

Connections AC power input: Neutrik PowerCon
DMX and RDM data in/out: 5-pin locking XLR
USB memory devices: USB host socket

Electrical	AC power: 120-240 V nominal, 50/60 Hz Power supply unit: Auto-ranging electronic switch-mode Typical half-cycle RMS inrush current: 16.2 A
Typical Power and Current	120 V, 60 Hz: 1225 W, 10.3 A, PF 0.999 208 V, 60 Hz: 1190 W, 5.8 A, PF 0.996 230 V, 50 Hz: 1186 W, 5.2 A, PF 0.994 240 V, 50 Hz: 1194 W, 5.0 A, PF 0.993 <i>Measurements made at nominal voltage. Allow for a deviation of +/- 10%.</i> <i>PF = power factor</i>
Thermal	Cooling: Filtered forced air (temperature-regulated, low noise) Maximum ambient temperature (Ta max.): 40° C Minimum ambient temperature (Ta min.): 5° C Maximum surface temperature, steady state, Ta=40° C: 150° C Total heat dissipation (calculated, +/- 10% at 120 V, 60 Hz): 4180 BTU/hr
Approvals	EU safety: EN 60598-2-17 (EN 60598-1), EN 62471 EU EMC: EN 55015, EN 55103-1, EN 55103-2, EN 61547 US safety: UL 1573 US EMC: FCC Part 15 Class A Canadian safety: CSA E598-2-17 (CSA E60598-1) Canadian EMC: ICES-003 Class A Australia/NZ: C-TICK N4241
Included Items	Lamp (installed): 97010346 Two Omega clamp attachment brackets with 1/4-turn fasteners: 91602001 Safety and installation manual: 35000258
Related Items	Martin USB Duo™ DMX Interface Box: 90703010 Martin RDM 5.5 Splitter™: 90758150
Spare Parts	Osram HTI 1000/PS Lok-it lamp: 97010346 Head air filter:
Ordering Information	MAC Viper™ Performance in cardboard box: 90233100 MAC Viper™ Performance in double flightcase: 90233110
Shipping Information	In cardboard carton Shipping dimensions (LxWxH): 580 mm x 450 mm x 870 mm Shipping weight: 41 kg Quantity on pallet: 8 fixtures Pallet dimensions (LxWxH): 1200 mm x 1000 mm x 1860 mm Pallet weight (incl. pallet): 350 kg In double flightcase

Published on: 8 Jul 2014. © 2013-2014 Martin Professional ApS. Specifications subject to change without notice