

ColorWash 2500E AT™

The ColorWash 2500E AT is newly equipped with a the Philips MSR Gold 1500 FastFit lamp, which makes it the most powerful Robe moving wash light fixture.

The ColorWash 2500E AT comes complete with CMY colour mixing system, variable CTO, 2 colour wheels and combined dimmer/shutter unit. The linear zoom has a range of 7° – 44°.

The ColorWash 2500E AT is an ideal tool for large live events and television shows and for all types of installations from multipurpose venues to large clubs.



Source

- Standard Lamp: MSR 1500 FastFit
- Lamp on request: MSR GOLD 1200 FastFit
- Base: PGJX50
- Control: Automatic and remote on/off
- Ballast: Electronic

Optical System

- High luminous glass reflector
- Zoom angle from 7° to 44°

Electromechanical Effects

- Cyan: 0–100%
- Magenta: 0–100%
- Yellow: 0–100%
- CTO: 0–100%
- Colour wheel 1: 6 replaceable "SLOT&LOCK" colours + open
- Colour wheel 2: 6 replaceable "SLOT&LOCK" colours + open
- Dimmer/Shutter: Full range dimming and variable strobe effect, Electronic strobing "ZAP"
- Zoom: 7° – 44° (standard front Fresnel lens), 87° (wide-angle front lens), 6° – 35° (front PC lens)
- Pan: 530°
- Tilt: 280°

Control and Programming

- Protocol: USITT DMX-512, RDM support
- Control channels: 17, 21, 23, 24 and 30
- DMX channels: 5 protocol modes
- Setting & Addressing: ROBE Navigation System (RNS)
- Built-in demo sequences
- Display: Blue/white LCD graphic
- Pan/Tilt resolution: 16bit
- Color wheel 1 positioning: 8 or 16bit

- Color wheel 2 positioning: 8 or 16bit
- Zoom: 8 or 16bit
- Dimmer: 8 or 16bit
- Controllable speed of fans
- Movement control: Tracking or vector
- Built-in analyzer for easy fault finding
- Ethernet port: Art-Net protocol, ready for ACN
- Data in/out: Locking 3-pin XLR & 5-pin XLR
- Stand-alone operation
- 3-editable programs, each up to 99 steps

Thermal

- Maximum ambient temperature (Ta): 40 °C (104 °F)
- Maximum surface temperature: 130 °C (266 °F)

Electrical Specification

- Wiring options: 208/230/250 V, 50/60 Hz
- Power consumption: 1670 VA at 230 V/50 Hz



Mechanical Specification

- Height: 641 mm (25.2 ") – head in horizontal position
- Width: 542 mm (21.3 ")
- Depth: 545 mm (21.5 ")
- Weight: 41 kg (90.4 lbs)

Rigging

- Mounting points: 8 pairs of ¼-turn locks
- Fastening system: ROBE's own 2x Omega clamps
- Fixation option: Pan/Tilt-lock mechanism

Optional Accessories

- Remote control IR
- Module of lens D200 PC
- Top Hats