

## ROBIN® 100 LEDBeam DL

These 'Pure White' versions of the popular LEDBeam 100 fixture have been added to compliment the range of Pure White LEDWash products. The LEDBeam utilises 12 x 15 W LEDs to provide an extra punchy 7 degree beam or with the addition of the clip on 25 or 40 degree frost filter, a flat, smooth wash. Small enough to 'hide' within a set, the LEDBeam 100 is ideal for use on exhibitions or in retail environments where a powerful, quality light is required with the added benefits of low power consumption and no lamp replacement or maintenance cost. The motorised Pan and Tilt system is equally capable of dramatic fast movement as it is a subtle slow sweep.

The DL model is fixed at 6500 K

Available only on request.



### Source

- Light source: 12 x 15 W DayLight LED multichips
- Life Expectancy: > 60.000 hours
- Typical Lumen Maintenance: 70% @ 60.000 hours

### Optical System and effects

- High efficiency component optics
- Beam angle 7°
- White colour temperature: 6500 K
- High resolution dimmer 0–100%
- Strobe effect, variable speed (20 flashes per second max.)
- Pre-programmed random strobe & pulse effects
- Pan and Tilt range: 450°/300°

### Control and Programming

- User Interface: 2 line LCD display & 4 push buttons
- Protocols: USITT DMX-512, RDM
- DMX modes (channels): 6 (16, 10, 12, 9, 16, 18)
- 3 user defined programs, each up to 25 steps
- Stand-alone operation
- Data in/out: Locking 5-pin XLR
- Built-in analyser for easy fault finding
- Optional wireless version available: CRMX technology from Lumen Radio

### Thermal Specification

- Maximum ambient temperature: 45 °C (113 °F)
- Maximum housing temperature: 75 °C (167 °F)

### Electrical Specification

- Supply Input: 100–240 V AC, 50–60 Hz auto ranging
- Power consumption: 200 W max.

- Power connection: Neutrik PowerCon In/Out



## Mechanical Specification

- Height: 314 mm (12.4")
- Width: 233 mm (9.2")
- Depth: 149 mm (5.9")
- Weight: 4 kg (8.8 lbs)

## Rigging

- 1 x Omega bracket (included) with ¼-turn quick locks

## Optional accessories

- Top hat
- Diffusion filter 20°
- Diffusion filter 40°
- Power Cable - Neutrik Powercon Input (2 m length)
- Power Cable - Neutrik Powercon Link (2 m length)